

Binder Test Plugs and Specification

- Combined Pressure/Temperature **"Binder"** Test Plugs. In Brass and 316 Stainless Steel

- Large Test Plug. • Small Test Plug. • Large Extended Plug. • Small Extended Plug.



- 15mm (½") BSPT. Type EP15
- 8mm (¼") BSPT. Type EP8



Type EP15SS Type EP8SS

- 15mm (½") BSPT. Type EP15EX & Type EP15EXSS

- 8mm (¼") BSPT. Type EP8EX & Type EP8EXSS

Thread: 15mm (½") BSPT.	Thread: 8mm (¼") BSPT.
O/A Length inc. Cap: 40 mm / Extended Plug 78mm.	O/A Length inc. Cap: 38mm / Extended Plug 75mm.
Max. Probe dia: 4mm.	Max. Probe dia: 4mm.

- **The extended plugs give approximately an extra 38.10mm (1½") for insulation.**

- Other lengths available to order. Add to type number in mm - **Example: EP 15 EX + 20mm.**

- **Standard Construction Types EP8 EP8EX EP15 EP15EX.**

- Body, cap and retaining ring: Brass.
- Cap seal: Neoprene Rubber.
- Retaining strap: Ethylene Propylene Rubber.
- Core: Ethylene Propylene Rubber.
- Max. Pressure: 35 BAR, 500 PSI.
- Temp range: -10°C up to +120°C.
- Suitable for low temperature hot water, chilled water and low temperature steam.

- **Also available "NITRILE VITON AND NEOPRENE CORES"**

Suitable For Some Oils, Gases and Other Fluids.

- Specifications may be changed without notice, 'Viton, Nitrile and Neoprene' are registered trade names from Dupont Limited.

- **Safety**

Binder Test Plugs and accessories are not recommended to be used on medium or high temperature hot water systems. Ethylene Propylene rubber is suitable for temperatures up to 135°C however if Plugs are used with injurious liquids or gases protective clothing i.e. long sleeved gloves, face and eye protection should be worn.

Ethylene Propylene, Nitrile Viton and Neoprene are proprietary materials and the information presented is believed to be accurate and reliable. We can assume no liability for results obtained or damage incurred through the application of the data. The information is intended as a guide. If in doubt ask for information on any of the above points.